




CE

---

Power	<b>27 W</b>	Voltage	<b>230 V</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>60 °</b>
Protection class	<b>IP20</b>		

---



 Declaration of Conformity



 3D model

MDR47PRO2784060LW

**Technical data:**

Product code	WOJP03867
Power	27 W
Nominal current	0.1291 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	3780 lm (360°)
Luminous flux**	3510 lm (360°)
Light efficiency	140 lm/W
Light colour	Neutral white
Beam angle	60 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	090x200x185 mm
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL
Other	L90B10 - 73000h ,



\*Applies to the LED source used. \*\*Luminaire luminous flux