

## MONA 4

W0JP04296

LED luminaire MONA 4, with a power of 40 W, high light efficacy 115 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.





Colour temperature3000 KColour of lightWWBeam angle60 °Degree of protection (IP)IP20	Power	40 W	Voltage	230 V
Beam angle <b>60</b> ° Degree of protection (IP) <b>IP20</b>	Colour temperature	3000 K	Colour of light	WW
	Beam angle	60 °	Degree of protection (IP)	IP20

## www.spectrumled.pl



## Technical data

Code	W0JP04296
Power	40 W
Nominal current	40 W 0.1913 mA
Voltaae	230 V
Energy consumption	230 V 40 kWh/1000h
Frequency	50HZ Hz
Protection class	
Power supply included	Yes
Manufacturer of power	BOKE
supply	DONL
Power factor	0.93
Useful luminous flux*	4600 lm (360°)
Luminous flux**	4400 lm (360°)
Lamp efficacy	115 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	60 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	0193x130 mm
Mounting hole	0160 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL
Catalogue number	CEL43PR04083060W_DIM

## Related documents



岸 User manual

