



---

Power	<b>46 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>110 °</b>	Degree of protection (IP)	<b>IP20</b>

---



 Photometric file

ALD2PRO468300PW\_DALI

**Technical data:**

Code	WOJP04706
Power	46 W
Nominal current	263 mA
Voltage	230 V
Energy consumption	46 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	OSRAM
Power factor	0.93
Useful luminous flux*	6670 lm (360°)
Luminous flux**	4400 lm (360°)
Lamp efficacy	145 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	110 °
RA	80
Light source included	+
Producer of LED diodes	SPECTRUM
Uniformity of color SDCM max	3
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	44x1710x35 mm
Mounting hole	1700x33,5 mm
Weight	3.24 kg
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL



\*applies to the LED source used. \*\*Luminaire luminous flux