



LED luminaire MONA 4, with a power of 27 W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>95. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.






Power	27 W	Voltage	230 V
Colour of light	BREAD	Beam angle	60 °
Degree of protection (IP)	IP20		

## www.spectrumled.pl



## Technical data

Code	W0JP05519
Power	27 W
Nominal current	129 mA
Voltage	230 V
	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power	OSRAM
supply Power factor	0.93
Useful luminous flux*	0.93 2565 lm (360°)
Luminnus flux**	2295 lm (360°)
Lamp efficacy	95 lm/W
Colour of light	BREAD
Beam angle	60 °
RA	95
Light source included	+
Producer of LFD diodes	CITIZEN
Uniformity of color SDCM max	3
Dimmahle	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	193x130 mm
Mounting hole	0160 mm
	Inside
Assembly method	Recessed
Application	Inside
Made in	PL
Catalogue number	CEL43PR027BREAD60W_DALI



## **Related documents**



岸 User manual