

# MONA 4

WQJP05654


LED luminaire MONA 4, with a power of 27 W, high light efficacy 140 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 36° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.



|                    |               |                           |                      |
|--------------------|---------------|---------------------------|----------------------|
| Power              | <b>27 W</b>   | Voltage                   | <b>230 V</b>         |
| Colour temperature | <b>4000 K</b> | Colour of light           | <b>Neutral white</b> |
| Beam angle         | <b>36 °</b>   | Degree of protection (IP) | <b>IP20</b>          |

## Technical data

|                              |                  |
|------------------------------|------------------|
| Code                         | WQJP05654        |
| Power                        | 27 W             |
| Nominal current              | 129.1 mA         |
| Voltage                      | 230 V            |
| Energy consumption           | 27 kWh/1000h     |
| Frequency                    | 50HZ Hz          |
| Protection class             | II               |
| Manufacturer of power supply | TCI              |
| Power factor                 | 0.93             |
| Useful luminous flux*        | 3780 lm (360°)   |
| Luminous flux**              | 2970 lm (360°)   |
| Lamp efficacy                | 140 lm/W         |
| Colour temperature           | 4000 K           |
| Colour of light              | Neutral white    |
| Beam angle                   | 36 °             |
| RA                           | 80               |
| Light source included        | +                |
| Producer of LED diodes       | CREE             |
| Uniformity of color SDCM max | 3                |
| Dimmable                     | OPC              |
| Working temperature range    | -20/+40 °        |
| Lifespan                     | 50000 h          |
| Housing material             | Aluminum         |
| Degree of protection (IP)    | IP20             |
| Colour                       | White            |
| Dimension (AxBxC)            | 193x130 mm       |
| Mounting hole                | Ø160 mm          |
| For use                      | Inside           |
| Assembly method              | Recessed         |
| Application                  | Inside           |
| Made in                      | PL               |
| Catalogue number             | CEL43PR02784060W |



## Related documents

 User manual Declaration of Conformity Photometric file