



|                  |                     |                    |                    |
|------------------|---------------------|--------------------|--------------------|
| Power            | <b>5 W</b>          | Voltage            | <b>230 V</b>       |
| Luminous flux*   | <b>480 lm (90°)</b> | Colour temperature | <b>2700-6500 K</b> |
| Light colour     | <b>CCT/RGB</b>      | Beam angle         | <b>50 °</b>        |
| Protection class | <b>IP20</b>         |                    |                    |




 User manual



 Declaration of Conformity

# Technical data:

|                              |                     |
|------------------------------|---------------------|
| Product code                 | W0JP06252           |
| Power                        | 5 W                 |
| Nominal current              | 45 mA               |
| Voltage                      | 230 V               |
| Energy efficiency classe     | E                   |
| Energy consumption           | 5 kWh/1000h         |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | +                   |
| Manufacturer of power supply | SMART               |
| Power factor                 | 0.5                 |
| Useful luminous flux*        | 480 lm (90°)        |
| Luminous flux**              | 480 lm (360°)       |
| Light efficiency             | 96 lm/W             |
| Luminous intensity           | 480 cd              |
| Colour temperature           | 2700-6500 K         |
| Light colour                 | CCT/RGB             |
| Beam angle                   | 50 °                |
| RA                           | 80                  |
| Light source included        | +                   |
| Uniformity of color SDCM max | 3                   |
| Dimmable                     | SMART               |
| Working temperature range    | -20/+40 °           |
| Lifespan                     | 17000 h             |
| Housing material             | Aluminum            |
| Protection class             | IP20                |
| Colour                       | White               |
| Dimension (axbxc)            | 50x175x145 mm       |
| For use                      | Inside              |
| Assembly method              | On 3-circuit system |
| Application                  | INT                 |
| Made in                      | PL                  |
| Other                        | RGBW ,              |



\*Applies to the LED source used. \*\*Luminaire luminous flux

\*Luminaire with the ability to change the color of light (2700 - 6500K) or dimming by application Spectrum SMART.