

# ALLDAY INSPIRE TWO

WQJP06579



See  
more

LED luminaire ALLDAY INSPIRE TWO, with a power of 39 W, high light efficacy 145 lm/W. It is part of the ALLDAY INSPIRE series, which is characterised by modern design, high-quality materials and a wide range of components and accessories that allow for the personalisation of the luminaires. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 80° gives directional light so that selected objects or surfaces can be better exposed. Designed for suspended mounting.



Power **39 W**  
Colour temperature **3000 K**  
Beam angle **80 °**

Voltage **230 V**  
Colour of light **WW**  
Degree of protection (IP) **IP20**

## Technical data

---

|                              |                     |
|------------------------------|---------------------|
| Code                         | WQJP06579           |
| Power                        | 39 W                |
| Nominal current              | 186 mA              |
| Voltage                      | 230 V               |
| Energy consumption           | 39 kWh/1000h        |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | Yes                 |
| Manufacturer of power supply | TRIDONIC            |
| Power factor                 | 0.93                |
| Useful luminous flux*        | 5655 lm (360°)      |
| Luminous flux**              | 4875 lm (360°)      |
| Lamp efficacy                | 145 lm/W            |
| Colour temperature           | 3000 K              |
| Colour of light              | WW                  |
| Beam angle                   | 80 °                |
| RA                           | 80                  |
| Light source included        | +                   |
| Producer of LED diodes       | SAMSUNG             |
| Uniformity of color SDCM max | 3                   |
| Dimmable                     | OPC                 |
| Working temperature range    | -20/+40 °           |
| Lifespan                     | 50000 h             |
| Housing material             | Aluminum            |
| Degree of protection (IP)    | IP20                |
| Colour                       | White               |
| Dimension (AxBxC)            | 1120X44X74 mm       |
| For use                      | Inside              |
| Assembly method              | Suspended           |
| Application                  | Inside              |
| Made in                      | PL                  |
| Other                        | L90B10 - 74000h ,   |
| Catalogue number             | ALD10PR03983080WW , |

## Related documents

---



User manual



Photometric file

