






| Power | 30 W | Voltage | 230 V |
|--------------------|--------|------------------|-------|
| Colour temperature | 3000 K | Light colour | WW |
| Beam angle | 115° | Protection class | IP20 |

LED PRO LUMINAIRE



Technical data:

| Product code | W0JP07829 |
|--------------------------------|-------------------------|
| Power | 30 W |
| Nominal current | 167 mA |
| Voltage | 230 V |
| Energy efficiency classe | D |
| Energy consumption | 30 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | Yes |
| Manufacturer of power supply | TRIDONIC |
| Power factor | 0.93 |
| Useful luminous flux* | 4350 lm (360°) |
| Luminous flux** | 2800 lm (360°) |
| Light efficiency | 145 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 115 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | SAMSUNG |
| Uniformity of color SDCM max | 3 |
| Dimmable | SMART |
| Working temperature range | -20/+40° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | Black |
| Dimension (axbxc) | 1120X57x57 mm |
| Mounting hole | 1126X45 mm |
| For use | Inside |
| Assembly method Application | Recessed Inside |
| Application Made in | PI |
| Mude III Other | PL L90B10 - 74000h , |
| oulei | LJUDIU 7400011, |



*Applies to the LED source used. **Luminaire luminous flux