



CE

Power **46 W**

Voltage **230 V**


Colour temperature **4000 K**

Light colour **WW**

Beam angle **50 °**

Protection class **IP20**



See more on dedicated page 



 3D model

ALD9PR04693050BB\_DALI

**Technical data:**

|                              |                          |
|------------------------------|--------------------------|
| Product code                 | WOJP09631                |
| Power                        | 46 W                     |
| Nominal current              | 220 mA                   |
| Voltage                      | 230 V                    |
| Energy consumption           | 55 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | I                        |
| Power supply included        | Yes                      |
| Manufacturer of power supply | TRIDONIC                 |
| Power factor                 | 0.93                     |
| Useful luminous flux*        | 5750 lm (360°)           |
| Luminous flux**              | 5750 lm (360°)           |
| Light efficiency             | 125 lm/W                 |
| Colour temperature           | 4000 K                   |
| Light colour                 | WW                       |
| Beam angle                   | 50 °                     |
| RA                           | 90                       |
| Light source included        | +                        |
| Producer of LED diodes       | SAMSUNG                  |
| Uniformity of color SDCM max | 3                        |
| Dimmable                     | DALI                     |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 50000 h                  |
| Housing material             | Aluminum                 |
| Protection class             | IP20                     |
| Colour                       | Black                    |
| Dimension (axbxc)            | 1680X44X74 mm            |
| For use                      | Inside                   |
| Assembly method              | On the ceiling/Suspended |
| Application                  | Inside                   |
| Made in                      | PL                       |
| Other                        | L90B10 - 74000h ,        |



\*Applies to the LED source used. \*\*Luminaire luminous flux