



CE

| Power | 27 W | Voltage | 230 V |
|------------------|-------|------------|-------|
| Light colour | BREAD | Beam angle | 24 ° |
| Protection class | IP20 | | |


SAL10PR027BREAD24B

LED PRO LUMINAIRE



Technical data:

| Due du et es de | |
|------------------------------|----------------|
| Product code | W0JP09860 |
| Power | 27 W |
| Nominal current | 129 mA |
| Voltage | 230 V |
| Energy consumption – | 27 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | OSRAM |
| Power factor | 0.93 |
| Useful luminous flux* | 2565 lm (360°) |
| Luminous flux** | 2295 lm (360°) |
| Light efficiency | 95 lm/W |
| Light colour | BREAD |
| Beam angle | 24 ° |
| RA | 95 |
| Light source included | + |
| Producer of LED diodes | CITIZEN |
| Uniformity of color SDCM max | 3 |
| Dimmable | OPC |
| Working temperature range | -20/+40° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | Black |
| Dimension (axbxc) | 187x150 mm |
| Mounting hole | 0175 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |
| | |



*Applies to the LED source used. **Luminaire luminous flux