



CE

Power **19 W**
Colour temperature **POULT K**
Beam angle **60 °**

Voltage **230 V**
Light colour **POULT**
Protection class **IP54/20**

CEL47PRO19POULT60W

Technical data:

| | |
|------------------------------|----------------|
| Product code | WOJP10700 |
| Power | 19 W |
| Nominal current | 91 mA |
| Voltage | 230 V |
| Energy consumption | 19 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | BRIDGELUX |
| Power factor | 0.93 |
| Useful luminous flux* | 2470 lm (360°) |
| Luminous flux** | 1900 lm (360°) |
| Light efficiency | 130 lm/W |
| Colour temperature | POULT K |
| Light colour | POULT |
| Beam angle | 60 ° |
| RA | 90 |
| Light source included | Yes |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP54/20 |
| Colour | White |
| Dimension (axbxc) | 230x74 mm |
| Mounting hole | Ø210 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |



*Applies to the LED source used. **Luminaire luminous flux