



CE

| Power | 27 W | Voltage | 230 V |
|--------------------|--------|------------------|---------|
| Colour temperature | FISH K | Light colour | FISH |
| Beam angle | 90 ° | Protection class | IP54/20 |


CEL47PR027FISH90W_DALI

LED PRO LUMINAIRE W0JP10887



Technical data:

| | MO 1010007 |
|------------------------------|-----------------------|
| Product code | WOJP10887 27 W |
| Power | _, |
| Nominal current | 129 mA 230 V |
| Voltage | 230 V 27 kWh/1000h |
| Energy consumption | 2, |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | TRIDONIC |
| Power factor | 0.93 |
| Useful luminous flux* | 3645 lm (360°) |
| Luminous flux** | 2430 lm (360°) |
| Light efficiency | 135 lm/W |
| Colour temperature | FISH K |
| Light colour | FISH |
| Beam angle | 90 ° |
| RA | 90 |
| Light source included | Yes |
| Producer of LED diodes | CITIZEN |
| Uniformity of color SDCM max | 3 |
| Dimmable | DALI |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP54/20 |
| Colour | White |
| Dimension (axbxc) | 230x74 mm |
| Mounting hole | 0210 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |



*Applies to the LED source used. **Luminaire luminous flux