



CE

| Power | 19 W | Voltage | 230 V |
|--------------------|--------|------------------|---------|
| Colour temperature | 3000 K | Light colour | 930 |
| Beam angle | 60 ° | Protection class | IP54/20 |


CEL47PR01993060W_DALI

LED PRO LUMINAIRE



Technical data:

| Product code | WOJP10906 |
|------------------------------|----------------|
| Power | 19 W |
| Nominal current | 91 mA |
| Voltage | 230 V |
| Energy consumption | 19 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Manufacturer of power supply | TRIDONIC |
| Power factor | 0.93 |
| Useful luminous flux* | 2280 lm (360°) |
| Luminous flux** | 1900 lm (360°) |
| Light efficiency | 120 lm/W |
| Colour temperature | 3000 K |
| Light colour | 930 |
| Beam angle | 60 ° |
| RA | 90 |
| Light source included | Yes |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Dimmable | DALI |
| Working temperature range | -20/+40° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP54/20 |
| Colour | White |
| Dimension (axbxc) | 230x74 mm |
| Mounting hole | 0210 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | Inside |
| Made in | PL |
| | |



*Applies to the LED source used. **Luminaire luminous flux