




Power **27 W**

Colour temperature **BREAD K**

Beam angle **60 °**

Voltage **230 V**

Light colour **BREAD**

Protection class **IP20**

CEL48PRO27BREAD60B\_DIM

#### Technical data:

|                              |                |
|------------------------------|----------------|
| Product code                 | WOJP11113      |
| Power                        | 27 W           |
| Nominal current              | 129 mA         |
| Voltage                      | 230 V          |
| Energy consumption           | 27 kWh/1000h   |
| Frequency                    | 50HZ Hz        |
| Protection class             | II             |
| Power supply included        | +              |
| Manufacturer of power supply | BOKE           |
| Power factor                 | 0.93           |
| Useful luminous flux*        | 2565 lm (360°) |
| Luminous flux**              | 2295 lm (360°) |
| Light efficiency             | 95 lm/W        |
| Colour temperature           | BREAD K        |
| Light colour                 | BREAD          |
| Beam angle                   | 60 °           |
| RA                           | 90             |
| Light source included        | Yes            |
| Producer of LED diodes       | CITIZEN        |
| Uniformity of color SDCM max | 3              |
| Dimmable                     | DIM            |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Protection class             | IP20           |
| Colour                       | Czarny         |
| Dimension (axbxc)            | 310x110 mm     |
| Mounting hole                | Ø260 mm        |
| For use                      | Inside         |
| Assembly method              | Recessed       |
| Application                  | Inside         |
| Made in                      | PL             |



\*Applies to the LED source used. \*\*Luminaire luminous flux