# SLI022009CW_IP44

IP20
IP44

90°

| | | | |
|---|---|---|---|
| Power | 25 W | Voltage | 230 V |
| Luminous flux* | 2125 lm (90°) | Colour temperature | 6000 K |
| Light colour | CW | Beam angle | 90 ° |
| Protection class | IP44/IP20*** | | |

Photometric file

3D model



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

# SLI022009CW_IP44

## Technical data:

| | |
|---|---|
| Product code | SLI022009CW_IP44 |
| Power | 25 W |
| Nominal current | 115 mA |
| Voltage | 230 V |
| Energy efficiency classe | F |
| Energy consumption | 25 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Useful luminous flux* | 2125 lm (90°) |
| Luminous flux** | 2000 lm (360°) |
| Light efficiency | 85 lm/W |
| Colour temperature | 6000 K |
| Light colour | CW |
| Beam angle | 90 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | - |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PLASTIC |
| Protection class | IP44/IP20*** |
| Colour | White |
| Dimension (axbxc) | 230x100 mm |
| Mounting hole | 210 mm |
| For use | Inside/Outside |
| Assembly method | Recessed |
| Made in | PRC |




*Applies to the LED source used. **Luminaire luminous flux
A version with CNBOP-PIB* certificate is also available (valid only in Poland).***Degree of protection [IP] (from the bottom/ from the top)



Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu