




Power	<b>150 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>13600 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>85 °</b>
IK	<b>08</b>	Protection class	<b>IP65</b>



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029058NW_PW
Power	150 W
Nominal current	655 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	13600 lm (120°)
Luminous flux**	13600 lm (360°)
Light efficiency	91 lm/W
Luminous intensity	7800 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Protection class	IP65
Colour	Gray
Dimension (axbxc)	360x262x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux